

[Get a Quote](#)

Overview

AR1220W(2GE WAN,8FE LAN,802.11b/g/n AP,2 USB,2 SIC)

Quick Specification

Model	AR1220W
Part Number	02353527
Memory	512 MB
Flash	256 MB
Service interfaces (standard configuration)	WAN interfaces: two GE electrical interfaces LAN interfaces: eight FE electrical interfaces and two Wi-Fi antenna interfaces
Extended slots	2xSIC
Weight	2.9 kg (6.39 lb)
Dimensions (W x D x H)	With no mounting bracket installed: 44.5 mm x 390.0 mm x 232.5 mm (1.75 in. x 15.35 in. x 9.15 in.) With mounting brackets installed: 44.5 mm x 482.6 mm x 232.5 mm (1.75 in. x 19.00 in. x 9.15 in.)

Product Details:


The Front Panel:



Datasheet

①	Two USB interfaces (host)
②	RST button
③	WLAN button
④	Two Wi-Fi antennas

The Back Panel:



⑤	Security lock
⑥	ESD jack
⑦	Two SIC slots
⑧	Product model silkscreen
⑨	Ground point
⑩	Two Wi-Fi antenna interfaces
⑪	CON/AUX interface
⑫	Mini USB interface
⑬	WAN interfaces: two GE electrical interfaces
⑭	LAN interfaces: eight FE electrical interfaces
⑮	PoE power jack
⑯	AC power jack
⑰	Jack for power cable locking strap

Get more information:

Do you have any question about the AR1220W 02353527?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Part Number	02353527
Model	AR1220W



Datasheet

First Supported Version	V200R001C01
Processor	Dual-core, 500 MHz
Memory	512 MB
Flash	256 MB
Micro SD card (default: sd1)	None
Hard disk	Not supported
Dimensions (H x W x D)	With no mounting bracket installed: 44.5 mm x 390.0 mm x 232.5 mm (1.75 in. x 15.35 in. x 9.15 in.) With mounting brackets installed: 44.5 mm x 482.6 mm x 232.5 mm (1.75 in. x 19.00 in. x 9.15 in.)
Weight	2.9 kg (6.39 lb)
Rated input voltage range (AC)	100 V to 240 V, 50 Hz/60 Hz
Maximum input voltage range (AC)	90 V to 264 V, 47 Hz to 63 Hz
Maximum input current	2 A
Maximum output power	60 W
RPS power supply	Not supported
PoE power supply	Supported (interfaces FE4 to FE7)
Typical power consumption	36 W
Maximum power consumption	42 W
Fans	Built-in fans, not pluggable
Airflow (facing the front panel)	Left to right
Management interfaces	1 (RJ45)
CON/AUX interfaces	1 (RJ45)
USB 2.0 interfaces	2
Service interfaces (standard configuration)	WAN interfaces: two GE electrical interfaces LAN interfaces: eight FE electrical interfaces and two Wi-Fi antenna interfaces
Extended slots	2xSIC
Operating temperature	0°C to 45°C (32°F to 113°F)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Operating relative humidity	5% to 95%, noncondensing
Operating altitude	< 5000 m (16404.2 ft.)



Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223