

[Get a Quote](#)

Overview

40GBase-LR4 Optical Transceiver, QSFP+,40GE, Single-mode Module (1310nm,10km, LC)

Quick Specification

Table 1 shows the Quick Specs.

Model	QSFP-40G-LR4
Part Number	02310MHS 02313URY
Description	40GBase-LR4 Optical Transceiver, QSFP+, 40GE, Single-mode Module (1310nm, 10km, LC)
Form Type	QSFP+
Wavelength	1310nm
Interface	LC duplex
Cable Type	SMF
CDR Support	Yes
TX Power	-7~2.3dBm
Commercial Temperature Range	0 to 70°C (32 to 158°F)
Max Data Rate	44.6Gbps
Max Cable Distance*	10km
Optical Components	DFB CWDM
DOM Support	Yes
Protocols	OTN OTU3, 40G Ethernet, Infini band, Fiber Channel, SATA/SAS3
Receiver Sensitivity	<-11.5dBm

Figure 1 shows the appearance.



Product Details

Compare to Similar Items

Table 2 shows the comparison of QSFP-40G-ER4, QSFP-40G-iSR4 and QSFP-40G-LR4.

Model	QSFP-40G-ER4	QSFP-40G-iSR4	QSFP-40G-LR4
Part Number	02311BKT	02310MHR	02310MHS
Description	40GBase-ER4 Optical Transceiver, QSFP+, 40G, Single-mode Module (1310nm, 40km, LC)	40GBase-iSR4 Optical Transceiver, QSFP+, 40G, Multimode (850nm, 0.15km, MPO) (Connect to four SFP+ Optical Transceiver)	40GBase-LR4 Optical Transceiver, QSFP+, 40GE, Single-mode Module (1310nm, 10km, LC)
Form Type	QSFP+	QSFP+	QSFP+
Wavelength	1310nm	850nm	1310nm
Max Data Rate	44.6Gbps	40Gbps	44.6Gbps
Max Cable Distance*	40km**	150m**	10km

Get More Information

Do you have any question about the QSFP-40G-LR4 (02310MHS 02313URY)?

Contact us now via info@hi-network.com.

Specification

QSFP-40G-LR4 Specification	
Basic Information	
Model	QSFP-40G-LR4
Part Number	02310MHS 02313URY
Description	40GBASE-LR4 optical transceiver, QSFP+, 40G, single-mode module (1310nm, 10km, LC)
Level-1 category	40GE QSFP+ Optical Modules
Technical Specifications	
Connector type	LC
Optical fiber type	SMF
Form factor	QSFP+

Transmission rate [bit/s]	40G
Target transmission distance [km]	Single-mode fiber (G.652) (with diameter of 9 μm): 10 km
Application standard/Type	40GBASE-LR4
Working case temperature [°C(°F)]	0°C to 70°C (32°F to 158°F)
Type of the end face of the fiber ceramic ferrule	PC or UPC
Center wavelength [nm]	1271, 1291, 1311, 1331
Overload power (AVG) [dBm]	3.3
Maximum Tx optical power (AVG) [dBm]	2.3
Minimum Tx optical power (AVG) [dBm]	-7.0
Minimum extinction ratio [dB]	3.5
Rx sensitivity (OMA) [dBm]	-11.5

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

