



Datasheet

[Get a Quote](#)

Overview

Huawei NE40E 50Gbit/s Bandwidth Flexible Card Line Processing Unit(LPUF-50,four sub-slots)

Quick Specification

Model	CR5DLPUF5070
Part Number	03054447
Description	Main Processing Unit D2(Including 2G Memory and 2G USB)
Attributes	Hardware
Dimensions (mm)	40.1(H) x 399.2(W) x 535.6(D)
Weight(kg)	8.2
Power consumption (typical value) (W)	169

Product Details:

Huawei ME0DBSUF5170

50Gbit/s bandwidth flexible card line processing unit(LPUF-50,four sub-slots) on Huawei NE40E.

Provides four slots that can hold two full-height FPICs or four half-height FPICs.

Supports a maximum bandwidth of 50 Gbit/s.

Automatic recovery of configurations.

Mixed use of different types of FPICs.

CR5DLPUF5070/LPUF-50 is a flexible line processing card applied to Huawei NE40E, supports a maximum bandwidth of 50 Gbit/s.

CR5DLPUF5070 comes with original box, if purchase together with router, it will be will inserted into the router by default when delivery, to economical volume weight.



Datasheet

The Front Panel:



Get more information:

Do you have any question about the CR5DLPUF5070 03054447?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Part Number	03054447
Model	CR5DLPUF5070
Description	Flexible Card Line Processing Unit(LPUF-50,four slots)
Attributes	Hardware
List Price(USD)	74,558.55
Category	Line Card
Product Line	Networking
Product Family	Router
Overview	Line Card
Sub Product Family	NetEngine NE80E Router
Product Series	NE80E(Enterprise Network)
UOM	PCS
Net Dimension(D*W*H mm)	511*398*40
Typic Power(W)	194
Reliability and availability	Software features Nonstop Forwarding (NSF) MPLS Fast Reroute (FRR) Hardware features The LPUF-50 or LPUF-50-L supports hot swap.

Datasheet

	The FPIC of the LPUF-50 or LPUF-50-L supports hot swap
NMS	Enhanced command-line interface SNMP and MIB support
Operating conditions	Long-term ambient temperature: 0°C to 45°C(32°F to 113°F) Short-term ambient temperature: -5°C to +55°C(23°F to 131°F) Long-term relative humidity: 5% to 85% Short-term relative humidity: 5% to 95%
Storage conditions	Storage temperature: -40°C to +70°C(-40°F to 158°F) Storage humidity: 5% to 95%

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223