

[Get a Quote](#)

## Overview

Optical Transceiver, eSFP, GE, BIDI Single-mode Module (TX1310/RX1490, 40km, LC)

## Quick Specification

Table 1 shows the Quick Specs.

Model	LE2MGSC40DE0
Part Number	02310KVV
Description	Optical Transceiver, eSFP, GE, BIDI Single-mode Module (TX1310/RX1490, 40km, LC)
Level-1 category	GE eSFP Optical Modules
Form factor	eSFP
Application standard	1000BASE-BX
Connector type	LC
Optical fiber type	SMF
Working case temperature [°C(°F)]	0°C to 70°C (32°F to 158°F)
Transmission rate [bit/s]	1 Gbit/s
Target transmission distance [km]	Single-mode fiber: 40 km
Center wavelength [nm]	1490 nm (RX) 1310 nm (TX)
Maximum Tx optical power [dBm]	3.0
Minimum Tx optical power [dBm]	-2.0
Minimum extinction ratio [dB]	9
Rx sensitivity [dBm]	-23
Overload power [dBm]	-3.0
Note	Supports the single-wire bidirectional function. Single-fiber bidirectional (BIDI) optical modules must be used in pairs. For example, LE2MGSC40DE0 must be used with LE2MGSC40ED0.

Figure 1 shows the appearance.



## Get More Information

Do you have any question about the LE2MGSC40DE0 (02310KVV)?

Contact us now via [info@hi-network.com](mailto:info@hi-network.com).

## Specification

LE2MGSC40DE0 Specification	
<b>Basic Information</b>	
Model	LE2MGSC40DE0
Part Number	02310KVV
Description	Optical Transceiver, eSFP, GE, BiDi Single-mode Module (TX1310/RX1490, 40km, LC)
Level-1 category	GE eSFP Optical Modules
<b>Technical Specifications</b>	
Connector type	LC
Optical fiber type	SMF
Form factor	eSFP
Transmission rate [bit/s]	1G
Target transmission distance [km]	Single-mode fiber: 40 km
Working case temperature [°C(°F)]	0°C to 70°C (32°F to 158°F)
Type of the end face of the fiber ceramic ferrule	PC or UPC
Center wavelength [nm]	1490(RX)1310(TX)
Overload power (AVG) [dBm]	-3.0

Maximum Tx optical power (AVG) [dBm]	3.0
Minimum Tx optical power (AVG) [dBm]	-2.0
Minimum extinction ratio [dB]	9
Rx sensitivity (OMA) [dBm]	-23
Note	Single-fiber bidirectional (BIDI) optical modules must be used in pairs. For example, LE2MGSC40DE0 must be used with LE2MGSC40ED0.

## Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

