

Get a Quote

Overview

The 10G SFP+ Passive Direct Attach Copper Twinax Cable is designed for use in 10GBASE Ethernet. This cable is compliant with IEEE 802.3, SFF-8431, and SFP+ MSA. With these features, this easy to install, high speed, cost-effective direct attach copper twinax cable is suitable for short-distance connectivity within a rack or between adjacent racks in data centers.

Quick Specification

Table 1 shows the Quick Specification.

Model	SFP-10G-CU5M
Part Number	02310QPR
Description	SFP+, 10G, High Speed Cable, 5m, SFP+20M, CC2P0.254B(S), SFP+20M, LSFZRH For Indoor
Connector X1	SFP+
Connector X2	SFP+
Cable length [m (ft.)]	5 m (16.40 ft.)
Electrical attribute	Passive
Bend radius [mm (in.)]	30 mm (1.18 in.)
Minimum Clearance for Cable Routing [mm (in.)]	60 mm (2.36 in.)

Figure 1 shows the appearance of SFP-10G-CU5M.



Get More Information

Do you have any question about the SFP-10G-CU5M (02310QPR)?

Contact us now via info@hi-network.com.

Specification

SFP-10G-CU5M Specification	
Model	SFP-10G-CU5M
Part Number	02310QPR
Description	SFP+, 10G, High Speed Cable, 5m, SFP+20M, CC2P0.254B(S), SFP+20M, LSFZRH For Indoor
Attributes	Hardware
Category	Optical Transceiver
Product Line	Networking
Product Family	Switch
Product Category	Optical Transceiver
Sub Product Family	Data Center Switch
Product Series	CE6800
EAN	6920702781776
UOM	PCS
Pack Weight(kg)	2
Pack Volume(m ³)	0.005159
Pack Dimension (D*W*H mm)	385*268*50
Net Dimension (D*W*H mm)	385*268*50

Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)


SFP-10G-CU5M (02310QPR)

Datasheet



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223