

Datasheet

[Get a Quote](#)

Overview

Huawei S5720-52X-EI-AC switch, Next-Generation Enhanced Gigabit Switches, supports a large capacity of 2 GB SDRAM and 4 x 10GE uplink ports.


Quick Specification

Model	S5720-52X-EI-AC
Part Number	02359589
Memory (RAM)	512 MB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
PoE	Not supported
Weight with packaging [kg(lb)]	9.5 kg (20.95 lb)
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 44.4 mm x 442.0 mm x 424.7 mm (1.75 in. x 17.4 in. x 16.72 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the handle on the rear panel): 44.4 mm x 442.0 mm x 451.8 mm (1.75 in. x 17.4 in. x 17.79 in.)

Datasheet

Product Details:

Appearance:



①	Forty-eight 10/100/1000BASE-T ports
②	Four 10GE SFP+ ports
③	One ETH management port
④	One mini USB port
⑤	One console port
⑥	One USB port
⑦	Ground screw
⑧	Two QSFP+ stack optical ports
⑨	RPS socket
⑩	AC socket

The Accessories for S5720-52X-EI-AC:

Recommended Transceivers:

Model	Description
40GE optical transceivers	
QSFP-40G-iSR4	40GBase-iSR4 Optical Transceiver, QSFP+, 40G, Multi-mode (850nm, 0.15km, MPO) (Connect to four SFP+ Optical Transceiver)
GE optical transceivers	

Datasheet

LE2MGSC40DE0	Optical Transceiver, eSFP, GE, BIDI Single-mode Module (TX1310/RX1490, 40km, LC)
LE2MGSC40ED0	Optical Transceiver, eSFP, GE, BIDI Single-mode Module (TX1490/RX1310, 40km, LC)
S-SFP-GE-LH40-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 40km, LC)
S-SFP-GE-LH40-SM1550	Optical Transceiver, eSFP, GE, Single-mode Module (1550nm, 40km, LC)
S-SFP-GE-LH80-SM1550	Optical Transceiver, eSFP, GE, Single-mode Module (1550nm, 80km, LC)
SFP-GE-BXU1-SC	1000Base,BIDI Optical Transceiver, SFP, GE, Single-mode Module (TX1490nm/RX1310nm, 10km, SC)
SFP-GE-LX-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 10km, LC)
SFP-GE-LX-SM1310-BIDI	Optical Transceiver, eSFP, GE, BIDI Single-mode Module (TX1310/RX1490, 10km, LC)
SFP-GE-LX-SM1490-BIDI	Optical Transceiver, eSFP, GE, BIDI Single-mode Module (TX1490/RX1310, 10km, LC)
SFP-GE-ZBXD1	Optical Transceiver, eSFP, GE, BIDI Single-mode Module (1570nm (Tx) / 1490nm (Rx), 80km, LC)
SFP-GE-ZBXU1	Optical Transceiver, eSFP, GE, BiDi Single-mode Module (1490nm (Tx) / 1570nm (Rx) ,80km, LC)
eSFP-GE-SX-MM850	Optical Transceiver, eSFP, GE, Multi-mode Module (850nm, 0.5km, LC)
eSFP-GE-ZX100-SM1550	Optical Transceiver, eSFP, GE, Single-mode Module (1550nm, 100km, LC)
GE-CWDM optical transceivers	
CWDM-SFPGE-1491	CWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1491nm, 80km, LC)
CWDM-SFPGE-1511	CWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1511nm, 80km, LC)
CWDM-SFPGE-1531	CWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1531nm, 80km, LC)
CWDM-SFPGE-1551	CWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1551nm, 80km, LC)
GE-DWDM optical transceivers	
DWDM-SFPGE-1542-14	DWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1542.14nm, 120km, LC)
DWDM-SFPGE-1542-94	DWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1542.94nm, 120km, LC)
DWDM-SFPGE-1543-73	DWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1543.73nm, 120km, LC)
DWDM-SFPGE-1544-53	DWDM Optical Transceiver, eSFP, 2.5G, Single-mode Module (1544.53nm, 120km, LC)
10GE SFP+ optical transceivers	
OMXD30000	Optical Transceiver, SFP+, 10G, Multi-mode Module (850nm, 0.3km, LC)
OSX010000	Optical Transceiver, SFP+, 10G, Single-mode Module (1310nm, 10km, LC)
OSX040N01	Optical Transceiver, SFP+, 10G, Single-mode Module (1550nm, 40km, LC)
OSXD22N00	Optical Transceiver, SFP+, 10G, Multi-mode Module (1310nm, 0.22km, LC, LRM)
SFP-10G-BXD1	10GBase, BIDI Optical Transceiver, SFP+, 10G, Single-mode Module (TX1330nm / RX1270nm, 10km, LC)
SFP-10G-BXU1	10GBase, BIDI Optical Transceiver, SFP+, 10G, Single-mode Module (TX1270nm / RX1330nm, 10km, LC)
SFP-10G-USR	10GBase-USR Optical Transceiver, SFP+, 10G, Multi-mode Module (850nm, 0.1km, LC)
SFP-10G-ZR	10GBase-ZR Optical Transceiver, SFP+, 10G, Single-mode Module (1550nm, 80km, LC)
SFP-10G-iLR	Optical Transceiver, SFP+, 9.8G, Single-mode Module (1310nm, 1.4km, LC)
10GE-CWDM optical transceiver	
SFP-10G-ZCW1471	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1471nm, 70km, LC)
SFP-10G-ZCW1491	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1491nm, 70km, LC)

Datasheet

SFP-10G-ZCW1511	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1511nm, 70km, LC)
SFP-10G-ZCW1531	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1531nm, 70km, LC)
SFP-10G-ZCW1551	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1551nm, 70km, LC)
SFP-10G-ZCW1571	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1571nm, 70km, LC)
SFP-10G-ZCW1591	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1591nm, 70km, LC)
SFP-10G-ZCW1611	Optical Transceiver, SFP+, 10G, Single-mode Module (CWDM, 1611nm, 70km, LC)
GE copper transceivers	
SFP-1000BaseT	Electrical Transceiver, SFP, GE, Electrical Interface Module (100m, RJ45)

Compare to Similar Items:

Models	S5720-52X-EI-AC	S5720-52P-EI-AC
Downlink Ports	48 x 10/100/1,000 Base-T Ethernet ports	48 x 10/100/1,000 Base-T Ethernet ports
Uplink Ports	4 x 10G SFP+ ports	4 x 1,000 Base-X SFP ports
PoE Support	N/A	N/A
Power Supply	AC power supply, supporting RPS	AC power supply, supporting RPS

Get more information:

Do you have any question about the S5720-52P-SI-AC 02359589?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Part Number	02359589
Model	S5720-52P-SI-AC
Memory (RAM)	512 MB
Flash	512 MB in total. To view the available flash memory size, run the display version command.
Mean time between failures (MTBF)	75.66 years
Mean time to repair (MTTR)	2
Availability	> 0.99999
Service port surge protection	Common mode: ± 6 kV
Power supply surge protection	Using AC power modules: ± 6 kV in differential mode, ± 6 kV in common mode Using DC power modules: ± 1 kV in differential mode, ± 2 kV in common mode
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 44.4 mm x 442.0 mm x 424.7 mm (1.75 in. x 17.4 in. x 16.72 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the handle on the rear panel):

Datasheet

	44.4 mm x 442.0 mm x 451.8 mm (1.75 in. x 17.4 in. x 17.79 in.)
Weight (with packaging)	9.5 kg (20.95 lb)
Stack ports	GE electrical ports and GE SFP optical ports on the front panel
RTC	Supported
RPS	Not supported
PoE	Not supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz -48 V DC to -60 V DC
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz -36 V DC to -72 V DC
Maximum power consumption (100% throughput, full speed of fans)	53.6 W
Typical power consumption (30% of traffic load) <ul style="list-style-type: none"> • Tested according to ATIS standard • EEE enabled • No PoE power consumption 	32.2 W
Operating temperature	0°C to 45°C (32°F to 113°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature	-5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5906 ft.)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Noise under normal temperature (27°C, sound power)	< 52 dB(A)
Relative humidity	5% to 95%, noncondensing
Operating altitude	AC power modules configured: 0-5000 m (0-16404 ft.) DC power modules configured: 0-2000 m (0-6562 ft.)
Certification	EMC certification Safety certification Manufacturing certification

Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)

S5720-52X-EI-AC (02359589)

Datasheet



HI-NETWORK.com
Your Global Original Network Supplier

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

