

Overview

The Cisco C1300-48FP-4G is a robust network switch that offers 48x 10/100/1000 PoE+ ports coupled with a substantial 740W power budget, ideal for powering a wide range of devices. Additionally, this switch features 4x Gigabit SFP uplink ports, making it a versatile solution for various networking environments. Perfect for businesses seeking reliable and scalable network infrastructure.

Quick Specification

Table 1 shows the quick specification.

Model	C1300-48FP-4G
Dimension	445 x 350 x 44 mm (17.5 x 13.78 x 1.73 in)
Weight	6.48 kg (14.28 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Ports	48x 10/100/1000 PoE+ ports with 740W power budget
Combo Ports	4x Gigabit SFP
Form Factor	Fixed Configuration

Figure 1 shows the appearance of C1300-48FP-4G.



Product Details

Product Features

- 48x 10/100/1000 PoE+ ports
- 740W total PoE power budget
- 4x Gigabit SFP uplink ports
- Advanced security features
- Energy-efficient design

Product Applications

- Powering IP phones and wireless access points in large office environments
- Supporting surveillance cameras and other security devices
- Enabling high-speed connections to servers and data centers

Supported Options

Accessory	Model
Stacking module	C1300-SM
Power Supply	C1300-PS
Rack Mount Kit	C1300-RMK

Compare to Similar Items

Model	Differences
Cisco C1200-48P-4X	Lower power budget (600W), 4x 10G SFP+ uplinks
Cisco C1400-24FP-4G	24 ports, same 740W power budget, 4x Gigabit SFP
Cisco C1500-48FP-8G	Higher power budget (960W), 8x Gigabit SFP uplinks

Get More Information

Do you have any questions about the C1300-48FP-4G?

Contact us now via info@hi-network.com.



Specification

C1300-48FP-4G Datasheet	
Ports	48x 10/100/1000 PoE+ ports with 740W power budget
Combo Ports	4x Gigabit SFP
Mounting	Rack-mountable
Forwarding Rate	77.38 Mpps
Switching Capacity	104.0 Gbps
Power	100-240V 50-60 Hz, internal, universal
PoE	Supported
Dimension	445 x 350 x 44 mm (17.5 x 13.78 x 1.73 in)
Weight	6.48 kg (14.28 lb)
Operating Temperature	23° to 122°F (-5° to 50°C)
Operating Humidity	10% to 90%, relative, noncondensing
Console port	Cisco standard RJ-45 console port and USB Type C port
USB port	USB Type C port on the front panel of the switch for easy file and image management as well as console port
Buttons	Reset button
Cabling type	Unshielded Twisted Pair (UTP) Category 5e or better for 1000BASE-T
LEDs	System, Link/Act, PoE, Speed
Flash	512 MB
CPU	ARM dual-core at 1.4 GHz
DRAM	1 GB DDR4
Certifications	UL (UL 62368), CSA (CSA 22.2), CE mark, FCC Part 15 (CFR 47) Class A

Want to Buy

Get a Quote

[Learn More](#) about Hi-Network[Search](#) our Resource Library[Follow](#) us on LinkedInContact for [Sales or Support](#)



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

