



## Overview

Cisco Catalyst 4503-E chassis offers 3 slots with Fan, one for supervisor engine slot, two for line-card slot with supporting up to 100 ports and up to 1500W POE power per slot. The solution provides centralized network architecture for enterprises-level, small and medium-size business through simplified operations. The highly intelligence performance offers non-blocking layer 2 - 4 switching with Secure, flexible communications. Any two Cisco Catalyst 4500E series Switches with Supervisor Engine 7L-E/7-E/8-E can be pooled together into a VSS, which doubles the system bandwidth, improves resiliency of the system and delivers the highest centralized reliable performance.

## Quick Specification

Product Code	WS-C4503-E
Supervisor engine slot	Slot 1
Line-card slots	2
Redundant power supplies	2
Backplane	48 Gbps full duplex per slot (96 Gbps)
Dimensions (H x W x D)	31.12 x 43.97 x 31.70 cm
Rack Units (RU)	7 RU
Weight	35 Kg
Airflow	Chassis fan tray: Right to left Power supply fan: Front to back



**Product Details:**

**The Front Panel:**



①	Redundant power supplies
②	Supervisor engine (slot 1)
③	Switching module (slots 2 and 3)
④	Fan tray assembly

**Cisco Catalyst 4506-E Switch Features**

Feature	Description
Chassis	Three horizontal slots. Slots are numbered from 1 (top) to 3 (bottom).
Supervisor engines	Supports the following supervisor engines: - Supervisor Engine 8-E - Supervisor Engine 7L-E - Supervisor Engine 7-E
Modules	Supports up to two Catalyst 4500 series modules.
Backplane	48 Gbps full duplex per slot (96 Gbps)
Fan tray	The chassis supports one hot-swappable fan tray.
Power supply	Supports one or two power supplies. All Catalyst 4500 series AC-input power supplies require single-phase source AC.

Get a Quote

## Accessories For WS-C4503-E:

### Recommended Elements:

Category	Model	Description
AP License	L-LIC-CTIOS-1A	1 AP Adder License for the IOS based Wireless Controller (e-delivery)
Primary Supervisor	WS-X45-SUP8-E	Catalyst 4500 E-Series Supervisor 8-E
	WS-X45-SUP7-E	Catalyst 4500 E-Series Supervisor, 848Gbps
	WS-X45-SUP7L-E	Catalyst 4500 E-Series Supervisor LE, 520Gbps
10/100/1000/MGig Line Cards	WS-X4748-RJ45-E	Cisco 4500 Line Card WS-X4748-RJ45-E Catalyst 4500 E-Series 48-Port 10/100/1000 Non-Blocking
	WS-X4748-UPOE+E	Cisco 4500 Line Card WS-X4748-UPOE+E Catalyst 4500E 48-Port UPOE 10/100/1000(RJ45)
	WS-X4748-RJ45V+E	Cisco 4500 Line Card WS-X4748-RJ45V+E Catalyst 4500E 48-Port PoE 802.3at 10/100/1000(RJ45)
1 G Fiber Line Cards	WS-X4724-SFP-E	Catalyst 4500 E-Series 24-Port GE (SFP)
	WS-X4748-SFP-E	Catalyst 4500 E-Series 48-Port GE (SFP)
	WS-X4712-SFP-E	Catalyst 4500 E-Series 12-Port GE (SFP)
10 G Fiber Line Cards	WS-X4606-X2-E	Catalyst 4500 E-Series 6-Port 10GbE (X2)
	WS-X4712-SFP+E	Catalyst 4500 E-Series 12-Port 10GbE (SFP+)
Power Supply	PWR-C45-1400AC	Catalyst 4500 1400W AC Power Supply (Data Only)
	PWR-C45-1400DC	C4500 1400W DC Triple Input SP Power Supply-data only
Supervisor Software License	L-C4500E-IP-ES=	Cisco Catalyst 4500E IP Base to Enterprise Services IOS upgrade license

### Compare To Similar Items:

Model	<a href="#">WS-C4503-E</a>	<a href="#">WS-C4506-E</a>
Supervisor engine slot	1	1
Line-card slots	2	5
Redundant power supplies	2	2
Supervisor engines	- Supervisor Engine 8-E - Supervisor Engine 7L-E - Supervisor Engine 7-E	- Supervisor Engine 8-E - Supervisor Engine 7L-E - Supervisor Engine 7-E
Backplane	48 Gbps full duplex per slot ( <b>96 Gbps</b> )	48 Gbps full duplex per slot ( <b>240 Gbps</b> )



Get more information:

Do you have any question about WS-C4503-E?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

## Specific Data Sheet:

Model Name	WS-C4503-E
Total number of slots	3
Line-card slots	2
Supervisor engine slots	1
Dedicated supervisor engine slot numbers	1
Supervisor engine redundancy	No
Supervisor engines supported	Supervisor Engines 8-E, 8L-E, 7-E, 7L-E, 6-E, and 6L-E
Maximum PoE per slot	1500W
Bandwidth scalability per line-card slot	Up to 48 Gbps on all slots
Number of power supply bays	2
AC input power	Yes
DC input power	Yes
Integrated PoE	Yes
Minimum number of power supplies	1
Power supplies supported	1000W AC 1400W AC 1300W ACV 2800W ACV 4200W ACV 6000W ACV 9000W ACV 1400W DC (triple input) 1400W-DC-P
Number of fan-tray bays	1
Location of 19-inch rack-mount	Front
Dimensions (H x W x D)	12.25 x 17.31 x 12.50 in. (31.12 x 43.97 x 31.70 cm)
Rack units (RU)	7RU
Chassis weight (with fan tray)	32.25 lb (14.63 kg)
Mounting	19- and 23-in. rack compatible (19-in. rack and cable guide hardware included)





## Want to Buy

---

[Get a Quote](#)[Learn More](#) about Hi-Network[Search](#) our Resource Library[Follow](#) us on LinkedInContact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

---

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

