

## Overview

The Huawei EchoLife EG8245Q is a routing-type ONT in the Huawei all-optical access solution. It uses the GPON technology to implement ultra-broadband access for users. It provides 4 GE+2 POTS+1 USB+2 WiFi (4 GE ports, 2 POTS ports, 1 USB port, 1 2.4G WiFi port and 1 5G WiFi port). The high forwarding performance ensures the user experience of voice, data and HD video services, and provides customers with an ideal all-optical access solution and future-oriented service support capability.

## Quick Specification

Table 1 shows the Quick Specification.

Model	EchoLife EG8245Q
Dimensions (W x D x H)	32 mm x 188 mm x 143 mm (without external antenna and pads)
Weight	About 320 g
Operating Temperature	0°C to 40°C
Operating Humidity	5% RH to 95% RH (non-condensing)
Power Adapter Input	100–240 V AC, 50–60 Hz
System Power Supply	11–14 V DC, 1.5 A
Static Power Consumption	5.2 W
Maximum Power Consumption	18 W
NNI	GPON
UNI	2POTS + 4GE + 2.4G/5G Wi-Fi + 1USB
Optical Connector	SC/APC
Indicators	POWER/PON/LOS/LAN/TEL/USB/WLAN/WPS

Figure 1 shows the appearance of EchoLife EG8245Q.





## Product Details

### Port Parameters

GPON Port	<ul style="list-style-type: none"> <li>• Class B+</li> <li>• Receiver sensitivity: -27 dBm</li> <li>• Overload optical power: -8 dBm</li> <li>• Wavelengths: US 1310 nm, DS 1490 nm</li> <li>• Wavelength blocking filter (WBF) of G.984.5</li> <li>• Flexible mapping between GEM Port and TCONT</li> <li>• GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>• Bi-directional FEC</li> <li>• SR-DBA and NSR-DBA</li> <li>• Type B (single-homing &amp; dual-homing)</li> </ul>
Ethernet Port	<ul style="list-style-type: none"> <li>• Ethernet port-based VLAN tags and tag removal</li> <li>• 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>• QinQ VLAN</li> <li>• Limit on the number of learned MAC addresses</li> <li>• MAC address learning</li> <li>• Auto-adaptive 10 Mbit/s, 100 Mbit/s or 1000 Mbit/s</li> </ul>
POTS Port	<ul style="list-style-type: none"> <li>• Maximum REN: 4</li> <li>• G.711A/μ, G.729a/b and G.722 encoding/decoding</li> <li>• T.30/T.38/G.711 fax mode</li> <li>• DTMF</li> <li>• Emergency calls (with the SIP protocol)</li> </ul>
USB Port	<ul style="list-style-type: none"> <li>• USB2.0</li> <li>• FTP-based network storage</li> <li>• File/Print sharing based on SAMBA</li> <li>• DLNA function</li> </ul>
WLAN	<ul style="list-style-type: none"> <li>• IEEE 802.11 b/g/n (2.4G)</li> <li>• IEEE 802.11 a/n/ac (5G)</li> <li>• 3 × 3 MIMO (2.4G&amp;5G)</li> <li>• Antenna gain: 2 dBi</li> <li>• WMM/Multiple SSIDs/WPS</li> <li>• 2.4G&amp;5G concurrent</li> <li>• Air interface rate:450 Mbit/s (2.4G); 1300 Mbit/s(5G)</li> </ul>

### Function List

Smart Interconnection	<ul style="list-style-type: none"> <li>• Smart Wi-Fi coverage</li> <li>• SIP/H.248 auto-negotiation</li> </ul>
-----------------------	--





	<ul style="list-style-type: none"> <li>• Any port, any service</li> <li>• Parental control</li> <li>• L2/L3(IPv4) forwarding: 1G uplink, 2G downlink</li> </ul>
Smart Service	<ul style="list-style-type: none"> <li>• Scheduled Wi-Fi shutdown</li> <li>• Smart Wi-Fi sharing:</li> <li>Portal/802.1x authentication</li> <li>SoftGRE-based sharing</li> <li>• Association of one account with two POTS ports</li> </ul>
Smart O&M	<ul style="list-style-type: none"> <li>• IPTV video quality diagnosis</li> <li>• eMDI</li> <li>• Rogue ONT detection and isolation from the OLT</li> <li>• Call emulation, and circuit test and loop-line test</li> <li>• PPPoE/DHCP simulation testing</li> <li>• WLAN emulation</li> <li>• eSight management</li> </ul>
Layer 3 Features	<ul style="list-style-type: none"> <li>• PPPoE/Static IP/DHCP</li> <li>• NAT/NAPT</li> <li>• Port forwarding</li> <li>• ALG, UPnP</li> <li>• DDNS/DNS server/DNS client</li> <li>• IPv6/IPv4 dual stack, and DS-Lite</li> <li>• Static/Default routes</li> <li>• Multiple services on one WAN port</li> </ul>
Security	<ul style="list-style-type: none"> <li>• SPI firewall</li> <li>• Filtering based on MAC/IP/URL addresses</li> </ul>
Multicast	<ul style="list-style-type: none"> <li>• IGMP v2/v3 proxy/snooping</li> <li>• MLD v1/v2 snooping</li> </ul>
Common O&M	<ul style="list-style-type: none"> <li>• OMCI/Web UI/TR069</li> <li>• Variable-length OMCI messages</li> <li>• Dual-system software backup and rollback</li> </ul>
Power Saving	<ul style="list-style-type: none"> <li>• Indicator power saving</li> <li>• COC V5</li> </ul>
QoS	<ul style="list-style-type: none"> <li>• Ethernet port rate limitation</li> <li>• 802.1p priority</li> <li>• SP/WRR/SP+WRR</li> <li>• Broadcast packet rate limitation</li> </ul>
Humanized design	<ul style="list-style-type: none"> <li>• Support one button to turn off all LEDs</li> </ul>

## Get More Information

Do you have any question about the EchoLife EG8245Q?

Contact us now via [info@hi-network.com](mailto:info@hi-network.com).





## Specification

EchoLife EG8245Q Specification	
Dimensions (W x D x H)	32 mm x 188 mm x 143 mm (without external antenna and pads)
Weight	About 320 g
Operating Temperature	0°C to 40°C
Operating Humidity	5% RH to 95% RH (non-condensing)
Power Adapter Input	100–240 V AC, 50–60 Hz
System Power Supply	11–14 V DC, 1.5 A
Static Power Consumption	5.2 W
Maximum Power Consumption	18 W
NNI	GPON
UNI	2POTS + 4GE + 2.4G/5G Wi-Fi + 1USB
Optical Connector	SC/APC
Indicators	POWER/PON/LOS/LAN/TEL/USB/WLAN/WPS
Installation mode	On the desk, or on the wall
Compliance certification	CE/WiFi
GPON Port	<ul style="list-style-type: none"> <li>• Class B+</li> <li>• Receiver sensitivity: -27 dBm</li> <li>• Overload optical power: -8 dBm</li> <li>• Wavelengths: US 1310 nm, DS 1490 nm</li> <li>• Wavelength blocking filter (WBF) of G.984.5</li> <li>• Flexible mapping between GEM Port and TCONT</li> <li>• GPON: consistent with the SN or password authentication defined in G.984.3</li> <li>• Bi-directional FEC</li> <li>• SR-DBA and NSR-DBA</li> <li>• Type B (single-homing &amp; dual-homing)</li> </ul>
Ethernet Port	<ul style="list-style-type: none"> <li>• Ethernet port-based VLAN tags and tag removal</li> <li>• 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission</li> <li>• QinQ VLAN</li> <li>• Limit on the number of learned MAC addresses</li> <li>• MAC address learning</li> <li>• Auto-adaptive 10 Mbit/s, 100 Mbit/s or 1000 Mbit/s</li> </ul>
POTS Port	<ul style="list-style-type: none"> <li>• Maximum REN: 4</li> <li>• G.711A/μ, G.729a/b and G.722 encoding/decoding</li> <li>• T.30/T.38/G.711 fax mode</li> <li>• DTMF</li> <li>• Emergency calls (with the SIP protocol)</li> </ul>





USB Port	<ul style="list-style-type: none"><li>• USB2.0</li><li>• FTP-based network storage</li><li>• File/Print sharing based on SAMBA</li><li>• DLNA function</li></ul>
WLAN	<ul style="list-style-type: none"><li>• IEEE 802.11 b/g/n (2.4G)</li><li>• IEEE 802.11 a/n/ac (5G)</li><li>• 3 × 3 MIMO (2.4G&amp;5G)</li><li>• Antenna gain: 2 dBi</li><li>• WMM/Multiple SSIDs/WPS</li><li>• 2.4G&amp;5G concurrent</li><li>• Air interface rate:450 Mbit/s (2.4G); 1300 Mbit/s(5G)</li></ul>

## Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

