

Get a Quote

Overview

Integrated Huawei MA5800 X2 main control board with 2-port 10GE/GE and 2-port GE optical uplink port

Quick Specification

Model	H901MPSG
Bandwidth per slot	40 Gbit/s (load sharing mode)
MAC address table	262143
ONT access	4096
multicast user	4096
static programs	8192
online programs	IPv4: 2000; IPv6: 2000

Product Details:

The Front Panel:





Compare To Similar Items:

Product Code	H901MPSA	H901MPSC	H901MPSG
Bandwidth per slot (load balancing mode)	40Gbit/s	80Gbit/s	40Gbit/s
Upstream or cascaded port	2*10GE/GE 2*GE	4*10GE/GE	2*10GE/GE 2*GE
Sync ETH clock	Yes	Yes	No
1588 ACR	No	No	No
1588v2 sync	Yes	Yes	No
ALM port (alarm digital parameters)	Yes	Yes	Yes
BITS/TOD port	Yes	Yes	Yes
Bandwidth per slot (load balancing mode)	40Gbit/s	80Gbit/s	40Gbit/s

Get more information:

Do you have any question about H901MPSG?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Model	H901MPSG
Bandwidth per slot	40 Gbit/s (load sharing mode)
MAC address table	262143
ONT access	4096
multicast user	4096
static programs	8192
online programs	IPv4: 2000; IPv6: 2000
IPv4 routing table	65536
IPv6 routing table	16384
service port	32768
ND table	16384
ARP table	32768
ALM port (alarm digital parameters)	Y (7 boolean value inputs and 1 boolean value output)
Environment	





[Get a Quote](#)

Operating Temperature	-40°C to +65°C
Energy consumption	Static: 26W Max: 41W
mechanical specification	
Dimensions (mm)	35.28 (L) x 258.15 (D) x 130.36 (H)
Weight (kg)	0.7

Want to Buy

[Get a Quote](#)



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223

