Get a Quote



Overview

The H901OXEG board is a 24-port 10GE/GE optical interface board, providing Ethernet optical access. It supports up to 24 channels of 10GE/GE P2P access services, and is applicable to Ethernet access.

Product Details:

The Front Panel:



Product Details:

The H901OXEG board supports the following features and specifications:

- \cdot 24 channels of 10GE/GE P2P optical access service
- $\cdot \ Upstream \ transmission \ (port \ network \ role \ UPLINK)$
- \cdot Cascading and aggregation
- \cdot GE port issuing synchronous Ethernet clock signals
- \cdot Temperature reading and high-temperature alarm
- \cdot Automatic power-off in case of high temperature
- \cdot Board power-off for energy conservation
- · D-CCAP



Get a Quote



Accessories For H901OXEG:

Supported Platforms:

Model	Description
EA5800-X17	Huawei SmartAX EA5800-X17, large-capacity, ETSI, supports 17 service slots
EA5800-X15	Huawei SmartAX EA5800-X15, large-capacity, IEC, supports 15 service slots
EA5800-X7	Huawei SmartAX EA5800-X7, medium-capacity, supports 7 service slots
<u>EA5800-X2</u>	Huawei SmartAX EA5800-X2, small-capacity, supports 2 service slots

Get more information:

Do you have any question about H901OXEG? Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Huawei SmartAX EA5800 24 port Aggregationed 10GE/GE Optical Interface Board

Want to Buy

Get a Quote



Learn More about Hi-Network

Search



Search our Resource Library



Follow us on LinkedIn



Contact for Sales or Support

Contact HI-NETWORK.COM For Global Fast Shipping



H901OXEG Datasheet

Get a Quote

HongKong Office Tel: +00852-66181601 HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com Skype: echo.hinetwork

WhatsApp Business: +8618057156223

