

Overview

The H901PILA board leads in one -48 V or -60 V DC power through two 100 A OT terminals, and transfers the power to the protection circuit, then to the filter circuit, and finally to the backplane, supplying power to the service subrack and other boards.

Quick Specification

Board	H901PILA
Description	Connect Power Board
Discount Category	Broadband Board
Product Line	Networking
Sub Product Family	FTTx and Cable
UOM	PCS
Net Dimension(D*W*H mm)	253*24*97
Typic Power(W)	2.3

Product Details:

The Front Panel:



Product Details:

The H901PILA board supports the following features and specifications:

- One -48 V or -60 V DC power input (input voltage range: -38.4 V to -72 V)
- Filtering and current-limiting for the power input port
- Power input detection and protection fuse fault detection
- Reporting of the protection alarm and board online signal

Accessories For H901PILA:

Supported Platforms:

Model	Description
EA5800-X17	Huawei SmartAX EA5800-X17, large-capacity, ETSI, supports 17 service slots
EA5800-X15	Huawei SmartAX EA5800-X15, large-capacity, IEC, supports 15 service slots
EA5800-X7	Huawei SmartAX EA5800-X7, medium-capacity, supports 7 service slots
EA5800-X2	Huawei SmartAX EA5800-X2, small-capacity, supports 2 service slots

Get more information:

Do you have any question about H901PILA?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Model	H901PILA
Description	Connect Power Board
Discount Category	Broadband Board
Product Line	Networking
Sub Product Family	FTTx and Cable
UOM	PCS
Net Dimension(D*W*H mm)	253*24*97
Typic Power(W)	2.3

Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223