

## Datasheet

[Get a Quote](#)

### Overview

Integrated DC Chassis Components (NE40E-X3)-4U Including Dual DC Power

### Quick Specification

Product Code	NE40E-X3 DC
Part Number	02351596
Model	CR52-BKPE-4U-DC
Switching Capacity	1.08 Tbit/s
Forwarding Performance	360 Mbit/s
Number of Slots	5 slots (for 3 LPUs and 2 MPUs)
Dimensions (H x W x D) mm	442 mm x 650 mm x 175 mm (DC, 4U)
Weight in Full Configuration	42 kg (DC)

### Product Details:

#### The Front Panel:



## Datasheet

### The Back Panel:



Get more information:

Do you have any question about the NE40-X3 DC 02351596?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

### Specific Data Sheet:

Product Name	NE40-X3 DC
Part Number	02351596
Model	CR52-BKPE-4U-DC
First supported version	V800R007C00
Switching Capacity	1.08 Tbit/s
Forwarding Performance	360 Mbit/s
Number of Slots	5 slots (for 3 LPUs and 2 MPUs)
Interface Types	100 GE/40 GE 10 GE- LAN/WAN GE/FE OC-192c/STM-64c POS OC-48c/STM-16c POS OC-12c/STM-4c POS OC-3c/STM-1cPOS Channelized OC-3/STM-1 Channelized STM-4 OC-3c/STM-1c ATM OC-12c/STM-4c ATM

## Datasheet

	<p>E3/T3</p> <p>CE1/CT1</p>
IPv4	<p>Support for static routing as well as dynamic routing protocols, such as RIP, OSPF, IS-IS, and BGP-4</p> <p>Line rate forwarding on all interfaces in complex routing environments, for example, when route flapping occurs</p>
IPv6	<p>Various IPv4-to-IPv6 transition technologies: manual tunnel, automatic tunnel, 6to4 tunnel, GRE tunnel, and ISATAP tunnel</p> <p>IPv4 over IPv6 tunnel and IPv6 Provider Edge (6PE)</p> <p>IPv6 static routes and dynamic routing protocols, such as BGP4+, RIPng, OSPFv3, and IS-ISv6</p> <p>IPv6 neighbor discovery, PMTU discovery, TCP6, ping IPv6, tracer IPv6, socket IPv6, static IPv6 DNS, IPv6 DNS server, TFTP IPv6 client, and IPv6 policy-based routing</p> <p>Internet Control Message Protocol Version 6 (ICMPv6), Management Information Base (MIB), User Datagram Protocol Version 6 (UDP6) MIB, TCP6 MIB, and IPv6 MIB</p> <p>L2NAT, NAT444, DS-Lite, and NAT64</p>
MPLS	<p>MPLS TE and MPLS/BGP VPN, in compliance with RFC 2547</p> <p>Inter-AS VPN Option A/B/C</p> <p>Integration with Internet services</p> <p>Martini and Kompella MPLS L2VPN</p> <p>L2VPN techniques, such as VPLS and VLL</p> <p>IP interworking over heterogeneous media</p> <p>Multicast VPN</p> <p>MPLS-TP, EVPN, Remote LFA</p>
Layer 2 Features	<p>IEEE 802.1Q, IEEE802.1ad, IEEE 802.1D, IEEE 802.1w, and IEEE 802.1s</p> <p>VLAN aggregation (super VLAN)</p> <p>Filtering list based on MAC addresses and ports</p> <p>1483B</p>
Reliability	<p>IP/LDP/VPN/TE/VLL FRR</p> <p>Protection mechanisms such as IP/TE auto rerouting, IGP/BGP/multicast route convergence, VRRP, RRPP, IP-Trunk load balancing and backup, BFD, MPLS/Ethernet OAM, Y.1731, and routing protocol/port/VLAN damping</p> <p>PW redundancy, E-Trunk, E-APS, and E-STP</p> <p>In-service patching for smooth software upgrade</p> <p>Passive backplane design</p> <p>Redundancy backup for key components, such as route processing modules, SFUs, and power modules to guard against single points of failure</p> <p>Switching between components that hot-back up each other</p> <p>GR, NSF, NSR, and ISSU</p> <p>Hot swap of all components</p>
QoS	<p>Well-designed HQoS and advanced scheduling and congestion avoidance technologies on each LPU</p> <p>Accurate traffic policing and traffic shaping</p> <p>Complex rule definition and fine-grained flow identification</p> <p>MPLS H-QoS, ensuring QoS for MPLS VPN, VLL, and PWE3 services</p> <p>8CT that combines MPLS TE and the DiffServ model</p> <p>TE-tunnel-oriented QoS</p>
OAM	<p>Y.1731, IP FPM, RFC 2544, MPLS OAM, 802.1ag, and 802.3ah, OPS</p>
Multicast	<p>IGMPv1, IGMPv2, and IGMPv3</p>



## Datasheet

	<p>Multicast routing protocols, including PIM-DM, PIM-SM, PIM-SSM, Multicast Source Discovery Protocol (MSDP), and Multiprotocol BGP (MBGP)</p> <p>Static multicast</p> <p>Multicast CAC</p> <p>Interoperability between multicast protocols</p> <p>Processing of multicast policies based on multicast routing protocols and multicast forwarding</p> <p>Multicast QoS and multicast replication for IPoE access users</p> <p>Two-level multicast replication on the SFUs and LPUs to optimize the multicast effect</p>
Security	<p>ACL-based packet filtering</p> <p>URPF</p> <p>GTSM</p> <p>DHCP snooping</p> <p>ARP attack defense and DoS attack defense</p> <p>MAC address limit and MAC-IP binding</p> <p>Secure Shell (SSH) and SSH version 2 (SSH v2)</p> <p>BGP-Flowspec</p> <p>RIPv2, OSPF, IS-IS, and BGP MD5, SHA256, Keychain</p>
Value-added Services	<p>IPsec tunnel</p> <p>Distributed GRE tunnel</p> <p>Distributed NetStream</p> <p>High-precision NAT: CGN</p>
Environment Requirements	<p>Long-term operating temperature: 0°C to 45°C</p> <p>Short-term operating temperature: -5°C to 55°C</p> <p>Long-term operating humidity: 5% RH to 85% RH</p> <p>Short-term operating humidity: 0% RH to 100% RH</p> <p>Operating altitude: ≤ 3,000 meters</p>
Dimensions (W x D x H)	442 mm x 650 mm x 175 mm (DC, 4U)
Power Consumption (in full configuration)	920W (DC)
Weight without packaging [kg(lb)]	15 kg (33.07 lb)
Weight (in full configuration)	42 kg (92.59 lb)
Typical power consumption (with configuration) [W]	<p>800 W (fully configured with LPUF-51s)</p> <p>920 W (fully configured with LPUF-120s)</p> <p>1239 W (fully configured with LPUF-241s)</p>
Typical heat dissipation (with configuration) [BTU/hour]	<p>2595.5 BTU/hour (fully configured with LPUF-51s)</p> <p>2984.9 BTU/hour (fully configured with LPUF-120s)</p> <p>4019.8 BTU/hour (fully configured with LPUF-241s)</p>
Power supply mode	DC built-in
Rated input voltage [V]	- 48 V/ - 60 V
Input voltage range [V]	- 38.4 V to - 72 V
Maximum input current [A]	42 A/single-module
Number of service board slots	3
Number of slots	5
Redundant MPUs	1:1



## Datasheet

Redundant power supply	1+1
Noise at normal temperature (acoustic power) [dB(A)]	ETSI-compliance (<72dBa @ 23° C (73.4° F))
Maximum number of power chassis inputs	(1 channel/PEM)*2 PEM=2 channels
Maximum input cable size	25 mm <sup>2</sup>
Front-end circuit breaker/fuse	50 A
Long-term operating temperature [° C(° F)]	0° C to 45° C (32° F to 113° F)
Short-term operating temperature [° C(° F)]	-5° C to 55° C (23° F to 131° F)
Storage temperature [° C(° F)]	-40° C to 70° C (-40° F to 158° F)
Restriction on the operating temperature variation rate [° C(° F)]	≤ 30° C/hour (86° F/hour)
Long-term operating relative humidity [RH]	5% RH to 85% RH, non-condensing
Short-term operating relative humidity [RH]	5% RH to 95% RH, non-condensing
Storage relative humidity [RH]	5% RH to 95% RH, non-condensing
Long-term operating altitude [m(ft.)]	≤ 4000 m (13123.2 ft.) (For the altitude in the range of 1800 m to 4000 m [5905.44 ft. to 13123.2 ft.], the operating temperature of the device must decrease by 1° C [1.8° F] for every 220 m [721.78 ft.]
Storage altitude [m(ft.)]	< 5000 m (16404 ft.)
MTBF [year]	27.44
MTTR [hour]	0.5
Availability	0.99999792

## Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601



NE40E-X3 DC (02351596)



**HI-NETWORK.com**  
Your Global Original Network Supplier

## Datasheet

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

