

Overview

A panel-type Optical Network Unit (ONU) that can be easily installed in 86-type electrical boxes on enterprise campuses, Huawei OptiXstar P871E is equipped with one Gigabit Passive Optical Network (GPON) or 10-Gigabit-Capable Symmetric Passive Optical Network (XGS-PON) port in the upstream direction, and two GE ports on the user side.

OptiXstar P871E series features multiple models: P871E with XGS-PON AC power, P871E-G with GPON AC power, and P871E-H with XGS-PON Advanced Fiber with Power (AFwP), which uses fibers for high-bandwidth connections and copper wires for power supply to remote optical devices.

Quick Specification

Table 1 shows the Quick Specification.

Model	OptiXstar P871E-H
Dimensions (H x W x D)	Panel: 86 x 86 x 9.5 mm Internal module depth: 35 mm
Weight	Approximately 168 g
Operating Temperature	-5°C to +40°C
Operating Humidity	5-95% RH (non-condensing)
PoE Power Input	48-56 V DC Note: The copper wires in an AFwP transmit power in PoE mode and do not transmit data.
Water Proof Rating	IP20
Surge Protection	GE: common mode 2.5 kV; differential mode 2.5 kV AC power supply: common mode 6 kV; differential mode 4 kV DC power supply: common mode 4 kV; differential mode 2 kV
Maximum Power Consumption	7.2 W
NNI	XGS-PON
UNI	2 x GE

Figure 1 shows the appearance of OptiXstar P871E-H.



Product Details

Interface Parameters

XGS-PON Port	<ul style="list-style-type: none"> • Port type: SC/UPC • Complying with ITU-T G.987.1, Class N1/N2 • Receiver sensitivity: -9 dBm to -28 dBm • Overload optical power: -9 dBm • Transmission rate: upstream 9.953 Gbit/s, downstream 9.953 Gbit/s • Type B single-homing • Type B dual-homing (supported in Layer 2 forwarding)
Ethernet Electrical Port	<ul style="list-style-type: none"> • Port type: RJ-45 • Auto port speed (10/100/1000 Mbit/s) • Auto-MDI/MDIX • Configuration of the number of MAC addresses learned • VLAN transparent transmission/VLAN filtering

Features

Versatile Design	<ul style="list-style-type: none"> • Easy installation in 86-type electrical boxes, with XGS-PON AC power, GPON AC power, and XGS-PON AFwP options
High Reliability	<ul style="list-style-type: none"> • Type B dual-homing service protection, plus 802.1x and IPv6/IPv4 firewalls, ensuring device access and network security
Smart O&M	<ul style="list-style-type: none"> • Variable-length OMCI messages • Rogue ONU detection and self-regulation • Ring network detection • PPPoE/DHCP simulation testing

Get More Information

Do you have any question about the OptiXstar P871E-H?

Contact us now via info@hi-network.com.

Specification

OptiXstar P871E-H Specification	
Dimensions (H x W x D)	Panel: 86 x 86 x 9.5 mm Internal module depth: 35 mm



Weight	Approximately 168 g
Operating Temperature	-5°C to +40°C
Operating Humidity	5-95% RH (non-condensing)
PoE Power Input	48-56 V DC Note: The copper wires in an AFwP transmit power in PoE mode and do not transmit data.
Water Proof Rating	IP20
Surge Protection	GE: common mode 2.5 kV; differential mode 2.5 k AC power supply: common mode 6 kV; differential mode 4 kV DC power supply: common mode 4 kV; differential mode 2 kV
Maximum Power Consumption	7.2 W
NNI	XGS-PON
UNI	2 x GE
Installation Mode	Indoor 86-box installation
Compliance Certification	CE/CCC
XGS-PON Port	<ul style="list-style-type: none"> • Port type: SC/UPC • Complying with ITU-T G.987.1, Class N1/N2 • Receiver sensitivity: -9 dBm to -28 dBm • Overload optical power: -9 dBm • Transmission rate: upstream 9.953 Gbit/s, downstream 9.953 Gbit/s • Type B single-homing • Type B dual-homing (supported in Layer 2 forwarding)
Ethernet Electrical Port	<ul style="list-style-type: none"> • Port type: RJ-45 • Auto port speed (10/100/1000 Mbit/s) • Auto-MDI/MDIX • Configuration of the number of MAC addresses learned • VLAN transparent transmission/VLAN filtering

Want to Buy

[Get a Quote](#)


[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales](#) or [Support](#)





Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

