

Get a Quote

Overview

The HW QSFP-4SFP10G-CU1M Compatible 40G QSFP+ to 4 x 10G SFP+ Direct Attach Cable operates over passive copper, which requires no additional power to ensure quality connectivity. This breakout cable is compliant with SFF-8436, SFF-8431 and SFP+ & QSFP MSA standards.

It provides a connection of a 40G QSFP+ port on one end and to four 10G SFP+ ports on the other end and is suitable for cost-effective close-range interconnections within the equipment room of telecom operators or data centers, etc.

Quick Specification

Table 1 shows the Quick Specification.

Model	QSFP-4SFP10G-CU1M
Part Number	02310MUK
Description	QSFP+, 4SFP+10G, High Speed Direct-attach Cables, 1m, QSFP+38M, CC8P0.254B(S), 4*SFP+20M, Used indoor
Connector X1	QSFP+
Connector X2	4*SFP+
Cable length	1 m (3.28 ft.)
Electrical attribute	Passive
Bend radius	25 mm (0.98 in.)
Minimum Clearance for Cable Routing	QSFP+ end: 100 mm (3.94 in.) SFP+ end: 60 mm (2.36 in.)

Figure 1 shows the appearance of QSFP-4SFP10G-CU1M.



Get More Information

Do you have any question about the QSFP-4SFP10G-CU1M (02310MUK)?

Contact us now via info@hi-network.com.

Specification

QSFP-4SFP10G-CU1M Specification	
Model	QSFP-4SFP10G-CU1M
Part Number	02310MUK
Description	QSFP+, 4SFP+10G, High Speed Direct-attach Cables, 1m, QSFP+38M, CC8P0.254B(S), 4*SFP+20M, Used indoor
Connector X1	QSFP+
Connector X2	4*SFP+
Cable length	1 m (3.28 ft.)
Electrical attribute	Passive
Bend radius	25 mm (0.98 in.)
Minimum Clearance for Cable Routing	QSFP+ end: 100 mm (3.94 in.) SFP+ end: 60 mm (2.36 in.)

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223