

Get a Quote

## Overview

QSFP28, 100G, High Speed Direct-attach Cables, 3m, (QSFP28), CC8P0.254B(S), QSFP28, Used indoor

## Quick Specification

Table 1 shows the Quick Specification.

Model	QSFP28-100G-CU3M
Part Number	02311KNX
Description	QSFP28, 100G, High Speed Direct-attach Cables, 3m, (QSFP28), CC8P0.254B(S), QSFP28, Used indoor
Connector X1	QSFP28
Connector X2	QSFP28
Cable length [m (ft.)]	3 m (9.84 ft.)
Electrical attribute	Passive
Bend radius [mm (in.)]	70 mm (2.76 in.)
Minimum Clearance for Cable Routing [mm (in.)]	90 mm (3.54 in.)

Figure 1 shows the appearance of QSFP28-100G-CU3M.



## Get More Information

Do you have any question about the SFP-10G-CU1M5 (02311KNX)?

Contact us now via [info@hi-network.com](mailto:info@hi-network.com).

## Specification

QSFP28-100G-CU3M Specification	
<b>Basic Information</b>	
Model	QSFP28-100G-CU3M
Part Number	02311KNX
Description	QSFP28, 100G, High Speed Direct-attach Cables, 3m, (QSFP28), CC8P0.254B(S), QSFP28, Used indoor
Level-1 category	High Speed Cable
<b>Technical Specifications</b>	
Connector X1	QSFP28
Connector X2	QSFP28
Cable length [m (ft.)]	3 (9.84)
Electrical attribute	Passive
Bend radius [mm (in.)]	70 (2.76)
Minimum Clearance for Cable Routing [mm (in.)]	90 (3.54)

## Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223