

## Datasheet

[Get a Quote](#)

## Overview

Huawei S5700 series Ethernet switches are next-generation energy-saving GE switches designed to provide high-bandwidth access and Ethernet multi-service aggregation. Based on cutting-edge hardware and Huawei Versatile Routing Platform (VRP) software, the S5700 provides a large switching capacity, high reliability (double power slots and hardware Ethernet OAM), and high-density GE ports to accommodate 10 Gbit/s upstream transmissions. It also supports Energy Efficient Ethernet (EEE) and iStack.


## Quick Specification

Model	S5730S-48C-PWR-EI
Part Number	98010791
Memory	1 GB
Flash memory	512 MB in total. To view the available flash memory size, run the <b>display version</b> command.
PoE	Supported
Weight (including package)	7.5 kg (16.53 lb)
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 44.4 mm x 442.0 mm x 425.0 mm (1.75 in. x 17.4 in. x 16.73 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the handle on the rear panel): 44.4 mm x 442.0 mm x 451.3 mm (1.75 in. x 17.4 in. x 17.77 in.)

## Datasheet

### Product Details:

#### Appearance:



①	Twenty-four PoE+ 10/100/1000BASE-T ports
②	Eight 10GE SFP+ ports
③	One PNP button
④	One console port
⑤	One ETH management port
⑥	One USB port
⑦	Ground screw
⑧	ESN label
⑨	Rear card slot
⑩	Fan slot
⑪	Power module slot 2
⑫	Power module slot 1

### The Accessories For S5730S-48C-PWR-EI:

#### Recommended Products:

Model	Description

## Datasheet

<a href="#">OMXD30000</a>	Huawei Optical Transceiver OMXD30000, SFP+, 10G, Multi-mode Module (850nm, 0.3km, LC)
<a href="#">SFP-GE-LX-SM1310</a>	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 10km, LC)
OMXD30009	Transceiver, QSFP+, 1310nm, 41.25Gbps, -7dBm, 2.3dBm, -11.5dBm, LC, SMF, 10
<a href="#">ESFP-GE-SX-MM850</a>	Optical Transceiver, eSFP, GE, Multi-mode Module (850nm,0.5km, LC)

Get more information:

Do you have any question about the S5730S-48C-PWR-EI 98010791?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

## Specific Data Sheet:

Part Number	98010791
Model	S5730S-48C-PWR-EI
Memory (RAM)	1 GB
Flash	512 MB in total. To view the available flash memory size, run the <b>display version</b> command.
Mean time between failures (MTBF)	46.8 years
Mean time to repair (MTTR)	2 hours
Availability	> 0.99999
Service port surge protection	Common mode: $\pm 7$ kV
Power supply surge protection	Using 500 W AC power modules: $\pm 6$ kV in differential mode, $\pm 6$ kV in common mode Using 650 W DC power modules: $\pm 2$ kV in differential mode, $\pm 4$ kV in common mode
Dimensions (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 44.4 mm x 442.0 mm x 425.0 mm (1.75 in. x 17.4 in. x 16.73 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the handle on the rear panel): 44.4 mm x 442.0 mm x 451.3 mm (1.75 in. x 17.4 in. x 17.77 in.)
Weight (including package)	7.5 kg (16.53 lb)
Stack ports	Any 10GE SFP+ or 40GE QSFP+ ports Ports on the 2-port QSFP+ rear stack card
RTC	Supported
RPS	Not supported
PoE	Supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz -48 V DC to -60 V DC
Maximum voltage range	90 V AC to 264 V AC, 47 Hz to 63 Hz -38.4 V DC to -72 V DC
Maximum power consumption (100% throughput, full speed of fans)	Not providing the PoE function: 83.2 W (without card) 100% PoE loads: 967 W (system power consumption: 227.8 W, PoE: 739.2 W, without card)
Typical power consumption (30% of traffic load)	44.2 W (without card)
<ul style="list-style-type: none"> <li>Tested according to ATIS standard</li> </ul>	

## Datasheet

<ul style="list-style-type: none"> <li>• EEE enabled</li> <li>• No PoE power consumption</li> </ul>	
Operating temperature	0°C to 45°C (32°F to 113°F) at an altitude of 0-1800 m (0-5906 ft.)
Short-term operating temperature	-5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5906 ft.)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Noise under normal temperature (27°C, sound power)	< 57.4 dB(A)
Relative humidity	5% to 95%, noncondensing
Operating altitude	0-5000 m (0-16404 ft.)
Certification	EMC certification Safety certification Manufacturing certification

## Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

## Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

WhatsApp Business: +8618057156223