

Get a Quote

Overview

GE SFP LX Plug In, Module, Spare, MX, A2/A10, M320/T640/T320, M120

Quick Specification

Table 1 shows the Quick Specs.

Basic Information	
Part Number	02312UUB
Model	SFP-GE-SX-C
Description	Optical Transceiver, e SFP, GE, Multi-mode Module (850nm,0.55km, LC)
Level-1 category	GE e SFP Optical Modules
Module name	SFP-GE-SX-C
Technical Specifications	
Connector type	LC
Optical fiber type	MMF
Form factor	eSFP
Transmission rate [bit/s]	1 Gbit/s
Target transmission distance [km]	Multimode optical fiber (modal bandwidth: 160 MHz*km; diameter: 62.5 μm): 0.22 km Multimode optical fiber (OM1): 0.275 km Multimode optical fiber (modal bandwidth: 400 MHz*km; diameter: 50 μm): 0.5 km Multimode optical fiber (OM2): 0.55 km Multimode optical fiber (OM3): 1 km
Application standard	1000BASE-SX
Working case temperature [°C(°F)]	-20°C to +85°C (-4°F to +185°F)
Center wavelength [nm]	850
Maximum Tx optical power [dBm]	-2.5
Minimum Tx optical power [dBm]	-9.5
Overload power [dBm]	0
Minimum extinction ratio [dB]	9
Rx sensitivity [dBm]	-17

Figure 1 shows the appearance.



Get more information:

Do you have any question about the QSFP-40G-LR4 (02310MHS) ?

Contact us now via email: info@hi-network.com

Specification:

Basic Information	
Part Number	02312UUB
Model	SFP-GE-SX-C
Description	Optical Transceiver, e SFP, GE, Multi-mode Module (850nm,0.55km, LC)
Level-1 category	GE e SFP Optical Modules
Module name	SFP-GE-SX-C
Technical Specifications	
Connector type	LC
Optical fiber type	MMF
Form factor	e SFP
Transmission rate [bit/s]	1 Gbit/s
Target transmission distance [km]	Multimode optical fiber (modal bandwidth: 160 MHz*km; diameter: 62.5 μm): 0.22 km Multimode optical fiber (OM1): 0.275 km Multimode optical fiber (modal bandwidth: 400 MHz*km; diameter: 50 μm): 0.5 km Multimode optical fiber (OM2): 0.55 km Multimode optical fiber (OM3): 1 km
Application standard	1000BASE-SX
Working case temperature [°C(°F)]	-20°C to +85°C (-4°F to +185°F)
Center wavelength [nm]	850
Maximum Tx optical power [dBm]	-2.5
Minimum Tx optical power [dBm]	-9.5
Overload power [dBm]	0
Minimum extinction ratio [dB]	9
Rx sensitivity [dBm]	-17

Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales](#) or [Support](#)



Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223