



[Get a Quote](#)

## Overview

Cisco Catalyst 2960-Plus 48 Ports LAN Lite Switches, supporting 48 x 10/100 ports, are designed for branches, conventional office workspaces, and infrastructure networks.

## Quick Specification

Product Code	WS-C2960+48TC-S
Enclosure Type	Rack-mountable 1U
Feature Set	LAN Lite
Uplink Interfaces	2 (SFP or 1000BASE-T)
Ports	48 x 10/100 Ethernet Ports
Forwarding Bandwidth	16 Gbps
Forwarding Performance	6.5 Mpps
RAM	128MB
Flash Memory	64MB
Dimensions	4.4cm x 45.0cm x 24.2cm
Package Weight	8.0 Kg



## Product Details:

### The Front Panel:



Note:

- ① Switch LEDs
- ② Mode Button
- ③ 48\*10/100 ports
- ④ Dual-purpose ports

·The switch LEDs include SYST, RPS, Status, Duplex and Speed LED.

·Dual-purpose ports support SFP or 1000BASE-T uplink port.

### The Back Panel:



Note:

- ① RJ-45 console port
- ② Fan exhaust
- ③ RPS connector
- ④ AC power connector

## The Accessories for C2960+

### Modules and Cables:

Models	Description
<a href="#">CAB-CONSOLE-RJ45</a>	Console Cable 6ft with RJ45 and DB9F
<a href="#">GLC-SX-MMD</a>	1000BASE-SX SFP transceiver module, MMF, 850nm, DOM
<a href="#">GLC-LH-SM</a>	GE SFP, LC connector LX/LH transceiver

Get more information:

Do you have any question about the Cisco Catalyst C2960+48TC-S switch?

Contact us now via e-mail: [info@hi-network.com](mailto:info@hi-network.com)

## Specific Data Sheet:

10/100 Ethernet Interfaces	48
Uplink Interfaces	2 (SFP or 1000BASE-T)
Cisco IOS Software Feature Set	LAN Lite
Available PoE Power	N
Flash memory	64 MB
DRAM	128 MB
Forwarding bandwidth	16 Gbps
Maximum active VLANs	64
VLAN IDs available	4K
Maximum transmission unit (MTU) - L3 packet	9000 bytes
Jumbo frame - Ethernet frame	9018 bytes
Forwarding Rate: 64-Byte L3 Packets, Millions of packets per second	10.1
Dimensions (H x W x D)	1.73 x 17.70 x 9.52 in (4.4 x 45.0 x 24.2 cm)
Weight	8 lb (3.6 Kg)
Package Weight	17.64 lb (8.0 Kg)
Operating temperature up to 5000 ft (1500 m)	23° to 113°F(-5° to 45°C)
Operating temperature up to 10,000 ft (3000 m)	23° to 104°F(-5° to 40°C)
Short-term exception at sea level*	23° to 131°F(-5° to 55°C)
Short-term exception up to 5000 feet (1500 m)*	23° to 122°F(-5° to 50°C)



Short-term exception up to 10,000 feet (3000 m)*	23° to 113°F(-5° to 45°C)
Short-term exception up to 13,000 feet (4000 m)*	23° to 104°F(-5° to 40°C)
Storage temperature up to 15,000 feet (4573 m)	23° to 158°F(-25° to 70°C)
Operating altitude	Up to 10,000 Feet(Up to 3,000 Meters)
Storage altitude	Up to 13,000 Feet(Up to 4,000 Meters)
Operating relative humidity	10% to 95% noncondensing
Storage relative humidity	10% to 95% noncondensing
Sound Pressure, dBA	Typical, LpAm: 41 Maximum, LpAD: 44
Sound Power, dbA	Typical, LwA: 51 Maximum, LwAD: 54
MTBF in thousands of hours	623
Ethernet Interfaces	10BASE-T ports: RJ-45 connectors, 2-pair Category 3, 4, or 5 unshielded twisted-pair (UTP) cabling 100BASE-TX ports: RJ-45 connectors, 2-pair Category 5 UTP cabling 1000BASE-T ports: RJ-45 connectors, 4-pair Category 5 UTP cabling 1000BASE-T SFP-based ports: RJ-45 connectors, 4-pair Category 5 UTP cabling
Indicator LEDs	Per-port status: Link integrity, disabled, activity, speed, and full duplex System status, Port Status, PoE, RPS, link duplex, and link speed
Console	Cisco Catalyst console cables: CAB-CONSOLE-RJ45 Console cable 6 ft. with RJ-45
Power	The internal power supply is an auto-ranging unit and supports input voltages between 100 and 240V AC. Use the supplied AC power cord to connect the AC power connector to an AC power outlet. The Cisco RPS connector offers connection for an optional Cisco RPS 2300 that uses AC input and supplies DC output to the switch. Only the Cisco RPS 2300 (model PWR-RPS2300) should be attached to the redundant-power-system receptacle
Management	BRIDGE-MIB CISCO-CABLE-DIAG-MIB CISCO-CDP-MIB CISCO-CLUSTER-MIB CISCO-CONFIG-COPY-MIB CISCO-CONFIG-MAN-MIB CISCO-DHCP-SNOOPING-MIB CISCO-ENTITY-VENDORTYPE-OID-MIB CISCO-ENVMON-MIB CISCO-ERR-DISABLE-MIB CISCO-FLASH-MIB CISCO-FTP-CLIENT-MIB CISCO-IGMP-FILTER-MIB CISCO-IMAGE-MIB CISCO-IP-STAT-MIB CISCO-LAG-MIB CISCO-MAC-NOTIFICATION-MIB





	<p>CISCO-MEMORY-POOL-MIB                  CISCO-PAGP-MIB                  CISCO-PING-MIB                  CISCO-POE-EXTENSIONS-MIB                  CISCO-PORT-QOS-MIB                  CISCO-PORT-SECURITY-MIB                  CISCO-PORT-STORM-CONTROL-MIB                  CISCO-PRODUCTS-MIB                  CISCO-PROCESS-MIB                  CISCO-RTTMON-MIB                  CISCO-SMI-MIB                  CISCO-STP-EXTENSIONS-MIB                  CISCO-SYSLOG-MIB                  CISCO-TC-MIB                  CISCO-TCP-MIB                  CISCO-UDLDP-MIB                  CISCO-VLAN-IFTABLE                  RELATIONSHIP-MIB                  CISCO-VLAN-MEMBERSHIP-MIB                  CISCO-VTP-MIB                  ENTITY-MIB                  ETHERLIKE-MIB                  IEEE8021-PAE-MIB                  IEEE8023-LAG-MIB                  IF-MIB                  INET-ADDRESS-MIB                  OLD-CISCO-CHASSIS-MIB                  OLD-CISCO-FLASH-MIB                  OLD-CISCO-INTERFACES-MIB                  OLD-CISCO-IP-MIB                  OLD-CISCO-SYS-MIB                  OLD-CISCO-TCP-MIB                  OLD-CISCO-TS-MIB                  RFC1213-MIB                  RMON-MIB                  RMON2-MIB                  SNMP-FRAMEWORK-MIB                  SNMP-MPD-MIB                  SNMP-NOTIFICATION-MIB                  SNMP-TARGET-MIB                  SNMPv2-MIB                  TCP-MIB                  UDP-MIB                  ePM MIB</p>
Standards	<p>IEEE 802.1D Spanning Tree Protocol                  IEEE 802.1p CoS Prioritization</p>





	<p>IEEE 802.1Q VLAN</p> <p>IEEE 802.1s</p> <p>IEEE 802.1w</p> <p>IEEE 802.1X</p> <p>IEEE 802.1ab (LLDP)</p> <p>IEEE 802.3ad</p> <p>IEEE 802.3af</p> <p>IEEE 802.3ah (100BASE-X single/multimode fiber only)</p> <p>IEEE 802.3x full duplex on 10BASE-T, 100BASE-TX, and 1000BASE-T ports</p> <p>IEEE 802.3 10BASE-T</p> <p>IEEE 802.3u 100BASE-TX</p> <p>IEEE 802.3ab 1000BASE-T</p> <p>IEEE 802.3z 1000BASE-X</p> <p>RMON I and II standards</p> <p>SNMP v1, v2c, and v3</p>
<p>RFC compliance</p>	<p>RFC 768 - UDP</p> <p>RFC 783 - TFTP</p> <p>RFC 791 - IP</p> <p>RFC 792 - ICMP</p> <p>RFC 793 - TCP</p> <p>RFC 826 - ARP</p> <p>RFC 854 - Telnet</p> <p>RFC 951 - Bootstrap Protocol (BOOTP)</p> <p>RFC 959 - FTP</p> <p>RFC 1112 - IP Multicast and IGMP</p> <p>RFC 1157 - SNMP v1</p> <p>RFC 1166 - IP Addresses</p> <p>RFC 1256 - Internet Control Message Protocol (ICMP) Router Discovery</p> <p>RFC 1305 - NTP</p> <p>RFC 1492 - TACACS+</p> <p>RFC 1493 - Bridge MIB</p> <p>RFC 1542 - BOOTP extensions</p> <p>RFC 1643 - Ethernet Interface MIB</p> <p>RFC 1757 - RMON</p> <p>RFC 1901 - SNMP v2C</p> <p>RFC 1902-1907 - SNMP v2</p> <p>RFC 1981 - Path MTU Discovery for IPv6</p> <p>RFC 2068 - HTTP</p> <p>RFC 2131 - DHCP</p> <p>RFC 2138 - RADIUS</p> <p>RFC 2233 - IF MIB v3</p> <p>RFC 2373 - IPv6 Aggregatable Addr</p> <p>RFC 2460 - IPv6</p> <p>RFC 2461 - IPv6 Neighbor Discovery</p> <p>RFC 2462 - IPv6 Autoconfiguration</p> <p>RFC 2463 - ICMP IPv6</p>





	<p>RFC 2474 - Differentiated Services (DiffServ) Precedence</p> <p>RFC 2597 - Assured Forwarding</p> <p>RFC 2598 - Expedited Forwarding</p> <p>RFC 2571 - SNMP Management</p> <p>RFC 3046 - DHCP Relay Agent Information Option</p> <p>RFC 3376 - IGMP v3</p> <p>RFC 3580 - 802.1X RADIUS</p>
Voltage (Autoranging)	100 to 240 VAC
Current (Amperes)	4.0 - 2.0
Frequency	50 to 60Hz
Power Rating (kVA)	0.46
DC Input Voltages (RPS Input)	3A at 12V (7A at -52V)
Power Consumption	<p>0% traffic: 51.1</p> <p>10% traffic: 50.8</p> <p>100% traffic: 51.4</p> <p>ATIS weighted average: 50.9</p>
Regulatory Compliance	Products should comply with CE Marking per directives 2004/108/EC and 2006/95/EC
Safety	<p>UL 60950-1 Second Edition</p> <p>CAN/CSA-C22.2 No. 60950-1 Second Edition</p> <p>EN 60950-1 Second Edition</p> <p>IEC 60950-1 Second Edition</p> <p>AS/NZS 60950-1</p>
EMC - Emissions	<p>47CFR Part 15 (CFR 47) Class A</p> <p>AS/NZS CISPR22 Class A</p> <p>CISPR22 Class A</p> <p>EN55022 Class A</p> <p>ICES003 Class A</p> <p>VCCI Class A</p> <p>EN61000-3-2</p> <p>EN61000-3-3</p> <p>KN22 Class A</p> <p>CNS13438 Class A</p>
EMC - Immunity	<p>EN55024</p> <p>CISPR24</p> <p>EN300386</p> <p>KN24</p>
Environmental	Reduction of Hazardous Substances (RoHS) including Directive 2011/65/EU



## Want to Buy?

---

Order Now

Get a Quote



Learn More about Hi-Network



Search our Resource Library



Follow us on LinkedIn



Contact for Sales or Support

## Contact HI-NETWORK.COM For Global Fast Shipping

---

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: [info@hi-network.com](mailto:info@hi-network.com)

Skype: echo.hinetwork

